

# DATA SHEET

Version: 01. June 2018



## Height-adjustment platelets, aluminium 0.2mm

Based on an aluminium foil / EN-AW 1050, 0/H111, AL 99.5

- Self-adhesive design
- Solvent-free acrylic adhesive
- Electrically conductive adhesive
- Adhesive with good final adhesion, suitable for use on construction sites

### Applications

- ▶ Double floor construction

### Technical data

**Substrate:** Pure aluminium, flexible, smooth, 0.200 mm thick

Tensile strength: 83 Rm = N/mm<sup>2</sup>

Elongation at break: A100 = 25.1 %

**Adhesive:** Synthetic resin acrylate, electrically conductive

Thickness of adhesive: 0.090 mm +/- 0.01 mm

Electrical conductivity:  
(on aluminium 99.5% 0.2 mm) Volume resistance < 10<sup>5</sup> ohm

Adhesive strength on steel: min. 20 N/25 mm (AFERA 5001)

Peel force based on FTM3: min. 500 mN/ 50mm

Heat resistance: -40°C to +90°C

Backing paper: Silicone coated paper

### Delivery standard

e.g. square: Cut sections on the roll, size: 20 x 20 mm  
Cut sections on the roll, size: 25 x 25 mm

e.g. triangular: Cut sections on the roll, size: 27 x 27 x 38 mm  
Cut sections on the roll, size: 40 x 40 x 57 mm

Cut sheets, tapes and punched parts, depending on the customer's requirements.  
Other material thicknesses and adhesive coatings also available.

The above values are intended as a guide or have been obtained under laboratory conditions and do not constitute any guarantee of product properties. We recommend carrying out preliminary tests to check that our products are suitable for use with other products. Under our General Terms and Conditions, we guarantee consistently high product quality, but due to the many possible applications we cannot accept any liability for specific results in practical applications. This data sheet supersedes any previous versions.